1.	**Description / Specification**	
1.1	Description	PP disposal bag (suitable for steam autoclaves)
1.2	Dimensions	*643201*: (width x length) 300 x 500 mm (± 10 mm) *644201*: (width x length) 400 x 780 mm (± 10 mm) *646201*: (width x length) 600 x 780 mm (± 10 mm) *649201*: (width x length) 700 x 1100 mm (± 10 mm) Foil thickness: 0,05 mm (± 10 %) Weight: *643201*: approx. 13 g *644201*: approx. 28 g *646201*: approx. 42 g *649201*: approx. 69 g
1.3	Volume	*643201*: 10 l (total volume), 6 l (useful capacity) *644201*: 30 l (total volume), 22 l (useful capacity) *646201*: 65 l (total volume), 32 l (useful capacity) *649201*: 130 l (total volume), 72 l (useful capacity)
1.4	Material / Resin	PP (Polypropylene)
1.5	Colour	translucent
1.6	Sterilisation	No
1.7	Quality Control	Product-Control: testing of attributive and variable characteristics in accordance with the valid specification
1.8	Other Information	For single use only

2.	**Features**	
2.1	Basic features	-
2.2	Temperature range	0℃ to +140℃
2.3	Autoclavability	Max. 134 ℃, 2 bar / 30 min (steam autoclaves) Max. 140 ℃, 120 min (hot-air sterilisers)
2.4	Centrifugation, max. RCF	N/A
2.5	Chemical Resistance	See homepage: www.gbo.com/bioscience →Products →Literature →Technical Information→Chemical Resistance of Resins
2.6	Shelf life	N/A
2.7	Other Information	- Cooling and UV light leads to embrittlement - The disposal bag should be closed loosely for sterilisation

3.	**Packaging**	**643 201, 644 201, 646 201**	**649 201**
3.1	Pieces / Bag	500	350
3.2	Pieces / Box	500	350
3.3	Lot-No.	Traceability by order confirmation number and batch number	
3.4	Other Information	-	

4.	**Other Information**
	-